

Delock USB 3.0 Dual Band WLAN ac/a/b/g/n Mini Stick 867 Mbps

Description

This wireless LAN USB Mini stick by Delock can be connected to a computer for the connection to a WLAN network. The WLAN stick can be connected to an AccessPoint or WLAN-router in a 2.4 GHz and 5 GHz band. Furthermore it enables an ad-hoc connection to a second computer.



Specification

- Connector: 1 x USB 3.0 Type-A male
- Chipset: Realtek RTL8812
- 1 x LED for activity
- 2T2R mode with 867 Mbps @ 5 GHz and 300 Mbps @ 2.4 GHz
- Frequency range: 2.4 GHz + 5 GHz band
- Antenna gain: 2 dBi
- Antenna type: PCB / PIFA
- Compatible with IEEE 802.11ac/a/n/b/g
- Encryption WEP, WPA, WPA2
- Transmission power (EIRP): 100 mW
- Supports DFS (Dynamic Frequency Selection)
- Dimensions incl. connector (LxWxH): ca. 43.5 x 27.0 x 11.6 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64,
Linux ex Kernel 3.17.8 / Kernel 4.9.4, Mac ex OS 10.12
- PC or laptop with a free USB Type-A port

Package content

- WLAN USB stick
- Driver CD
- User manual

Item no. 12502


EAN: 4043619125029

Country of origin: China

Package: Retail Box



Images



| Interface | |
|---------------------------|---|
| connector: | standard 1 x USB 3.0 Type-A male |
| Technical characteristics | |
| Chipset: | standard Realtek RTL8812 |
| Data transfer rate: | standard 867 Mbps @ 5 GHz @ 2T2R 300 Mbps @ 2.4 GHz @ 2T2R |
| Frequency range: | standard 2.4 GHz band 5 GHz band |
| Gain: | standard 2 dBi |
| Power handling: | standard 100 mW |
| Encryption: | standard WEP WPA WPA2 |
| WLAN standard: | standard 802.11ac 802.11n 802.11a 802.11b 802.11g |
| Physical characteristics | |
| Antenna type: | standard PCB PIFA |
| Length: | standard 43.5 mm |
| Width: | standard 27.0 mm |
| Height: | standard 11,6 mm |
| Colour: | standard black |